

(19)



JAPANESE PATENT OFFICE

# PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2005028046 A**

(43) Date of publication of application: **03.02.2005**

(51) Int. Cl. **A61B 17/56**  
**A61B 17/60, A61C 7/00**

(21) Application number: **2003273701**  
(22) Date of filing: **11.07.2003**

(71) Applicant: **KITAKYUSHU FOUNDATION FOR  
THE ADVANCEMENT OF  
INDUSTRY SCIENCE &  
TECHNOLOGY**

(72) Inventor: **TOMINAGA KAZUHIRO**

## (54) BONE POSITIONING DEVICES


### (57) Abstract:

**PROBLEM TO BE SOLVED:** To provide a bone positioning device for positioning a bone in an operation through the use of a simple method by using a member with a simple structure.

**SOLUTION:** The bone positioning device 10 stores relative positions between a first bone 11 and a second bone 12 being movable with respect to the first bone 11. The apparatus includes a freely bendable tube 14 formed to be partially freely extending/contracting possible; a first rigid body 16a for connecting one end of the tube 14 to the first bone 11; a second rigid body 16b for connecting the other end of the tube 14 to the second bone; and a filler which is filled in the tube 14,

and hardened by a prescribed processing after positioning the relative positions of the first and second bones 11, 12, so as to hold the tube 14 in a fixed shape. Consequently, the relative positions of the first and second bones 11, 12 are determined and held.

**COPYRIGHT: (C)2005,JPO&NCIPI**



PUBLICATION NUMBER : 2005028046  
PUBLICATION DATE : 03-02-05


APPLICATION DATE : 11-07-03  
APPLICATION NUMBER : 2003273701

APPLICANT : KITAKYUSHU FOUNDATION FOR THE  
ADVANCEMENT OF INDUSTRY  
SCIENCE & TECHNOLOGY;

INVENTOR : TOMINAGA KAZUHIRO;

INT.CL. : A61B 17/56 A61B 17/60 A61C 7/00

TITLE : BONE POSITIONING DEVICES



ABSTRACT : PROBLEM TO BE SOLVED: To provide a bone positioning device for positioning a bone in an operation through the use of a simple method by using a member with a simple structure.

SOLUTION: The bone positioning device 10 stores relative positions between a first bone 11 and a second bone 12 being movable with respect to the first bone 11. The apparatus includes a freely bendable tube 14 formed to be partially freely extending/contracting possible; a first rigid body 16a for connecting one end of the tube 14 to the first bone 11; a second rigid body 16b for connecting the other end of the tube 14 to the second bone; and a filler which is filled in the tube 14, and hardened by a prescribed processing after positioning the relative positions of the first and second bones 11, 12, so as to hold the tube 14 in a fixed shape. Consequently, the relative positions of the first and second bones 11, 12 are determined and held.

COPYRIGHT: (C)2005,JPO&NCIPI